

Safety Data Sheet

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision date: 28.05.2015

Version: 1.0

Print date: 31.05.2015

SECTION 1: Identification

Product identifier

Trade name/designation:	Isopropyl alcohol 70%
Product No.:	76432
Substance name:	2-Propanol (≥ 50%)
CAS No.:	67-63-0
INDEX No.:	000-000-00-0
REACH registration No.:	Not yet communicated down the supply chain.
Other means of identification:	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	General chemical reagent
---------------------------	--------------------------

Details of the supplier of the safety data sheet

United States of America

VWR Chemical Manufacturing LLC

Street	3 Lincoln Boulevard
Postal code/city	Rouses Point, NY 12979
Telephone	800-932-5000
Telefax	+1-610-728-2103
E-mail (competent person)	NAMSDS@vwr.com

Emergency telephone

Telephone	+1-800-424-9300 (Chemtrec, 24 hrs/day, 7 days/week, USA)
-----------	--

Canada

VWR Chemical Manufacturing LLC

Street	2360 Argentinia Rd.
Postal code/city	Mississauga, ON, L5N 5Z7
Telephone	800-932-5000
Telefax	+1-610-728-2103
E-mail (competent person)	NAMSDS@vwr.com

Emergency telephone

Telephone	+1-613-996-6666 (Canutec, 24 hrs/day, 7 days/week, Canada)
-----------	--

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according GHS

Hazard classes and hazard categories	Hazard statements
Flammable liquid, category 2	H225
Eye irritation, category 2	H319
Specific target organ toxicity (single exposure), category 3, narcotic effect	H336

Classification according to Directive 67/548/EEC or 1999/45/EC

F	Highly flammable	R11
Xi	Irritant	R36
		R67

Label elements

Labelling according GHS

Hazard pictograms



Signal word: Danger

Hazard statements	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Labelling (67/548/EEC or 1999/45/EC)

Hazard symbols

F, Xi

R-phrases	
R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

S-phrases	
S7	Keep container tightly closed.
S16	Keep away from sources of ignition - No smoking.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Other hazards

SVHC No

SECTION 3: Composition / information on ingredients

Hazardous ingredients Classification according to the OSHA Hazard Communication Standard 29 CFR 1910.1200

Substance name	Concentration	Product identifier	Hazard classes and hazard categories
2-Propanol	>50%	CAS No.: EC No.: REACH No.: Not yet communicated down the supply chain.	Flammable liquid, category 2 - H225 Eye irritation, category 2 - H319 Specific target organ toxicity (single exposure), category 3, narcotic effect - H336

Hazardous ingredients Classification according to 67/548/EEC

Substance name	Concentration	Product identifier	Hazard classes and hazard categories
2-Propanol	>50%	CAS No.: EC No.: REACH No.: Not yet communicated down the supply chain.	F, Highly flammable, R11 Xi, Irritant, R36 R67

SECTION 4: First aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. Change contaminated, saturated clothing. Do not leave affected person unattended.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin reactions, consult a physician.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye. Remove contact lenses, if present and easy to do. Continue rinsing.

In case of ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Give nothing to eat or drink.

Most important symptoms and effects, both acute and delayed

no data available

Indication of any immediate medical attention and special treatment needed

no data available

Self-protection of the first aider

First aider: Pay attention to self-protection!

Information to physician

no data available

SECTION 5: Firefighting measures**Extinguishing media****Suitable extinguishing media**

Water spray ABC-powder Carbon dioxide (CO₂) Nitrogen

Extinguishing media which must not be used for safety reasons

no restriction

Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide

Advice for firefighters

DO NOT fight fire when fire reaches explosives. In case of fire: Wear self-contained breathing apparatus.

Additional information

Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Avoid generation of dust. Do not breathe dust/fume/gas/mist/vapours/spray. Provide adequate ventilation. Remove all sources of ignition. Use personal protection equipment. The accumulation in lowlying or closed rooms can cause increased danger of fire and explosion. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. In case of major fire and large quantities: Remove persons to safety.

Environmental precautions

Do not allow to enter into surface water or drains. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

Spilled product must never be returned to the original container for recycling. Prevent spread over a wide area (e.g. by containment or oil barriers). Soak up inert absorbent and dispose as waste requiring special attention.

Additional information

Clear spills immediately.

SECTION 7: Handling and storage**Precautions for safe handling**

Avoid: Inhalation Avoid contact with skin and eyes. Use extractor hood (laboratory). If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Keep away from sources of ignition. - No smoking. Usual measures for fire prevention. Take precautionary measures against static discharges. Protect from moisture.

Conditions for safe storage, including any incompatibilities

storage temperature: 15-25 °C

Storage class: 3

Keep container tightly closed in a cool, well-ventilated place. Always close containers tightly after the removal of product. Store product under (gas): Protective gas, dry Do not allow contact with air.

Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

Control parameters

Ingredient (Designation)	Regulatory information	Country	Limit value type (country of origin)	Limit value	Remark
2-Propanol	OSHA	US	LTV	980 mg/m ³ - 400 ppm	
2-Propanol	NIOSH	US	LTV	980 mg/m ³ - 400 ppm	
2-Propanol	NIOSH	US	STV	1225 mg/m ³ - 500 ppm	15 minutes average value

Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Personal protection equipment

Wear suitable protective clothing. When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Eye/face protection

Eye glasses with side protection DIN-/EN-Norms: DIN EN 166

Recommendation: VWR 111-0432

Skin protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Recommended glove articles DIN-/EN-Norms: DIN EN 374 In the case of wanting to use the gloves again, clean them before taking off and air them well.

By short-term hand contact

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,12 mm

Breakthrough time (maximum wearing time): 51 min

Recommended glove articles: VWR 112-0998

By long-term hand contact

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,38 mm

Breakthrough time (maximum wearing time): > 480 min

Recommended glove articles: VWR 112-3717 / 112-1381

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Suitable respiratory protection apparatus: Full-/half-/quarter-face masks (DIN EN 136/140)

Recommendation: VWR 111-0206

Suitable material: A2B2E2K2P3

Recommendation: VWR 111-0059

Additional information

Wash hands before breaks and after work. Avoid contact with skin and eyes. When using do not eat, drink or smoke. Provide eye shower and label its location conspicuously.

Environmental exposure controls

no data available

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

(a) Appearance

Physical state: liquid

Colour: colourless

(b) Odour: no data available

(c) Odour threshold: no data available

Safety relevant basic data

(d) pH: no data available

(e) Melting point/freezing point: no data available

(f) Initial boiling point and boiling range: no data available

(g) Flash point: 17 °C

(h) Evaporation rate: no data available

(i) Flammability (solid, gas): Highly flammable liquid and vapour.

(j) Upper/lower flammability or explosive limits

Lower explosion limit: no data available

Upper explosion limit: no data available

(k) Vapour pressure: no data available

(l) Vapour density: no data available

(m) Relative density: 0.8 - 0.92 g/cm³ (20 °C)

(n) Solubility(ies)

at 20 °C: no data available

Soluble (g/L) in: no data available

(o) Partition coefficient: n-octanol/water: no data available

(p) Auto-ignition temperature: no data available

(q) Decomposition temperature: no data available

(r) Viscosity

Kinematic viscosity: no data available

Dynamic viscosity: no data available

(s) Explosive properties: not applicable

(t) Oxidising properties: not applicable

Other information

Bulk density: no data available

Refraction index: no data available

Dissociation constant: no data available
Surface tension: no data available
Henry constant: no data available

SECTION 10: Stability and reactivity

Reactivity

no data available

Chemical stability

no data available

Possibility of hazardous reactions

no data available

Conditions to avoid

no data available

Incompatible materials

no data available

Hazardous decomposition products

no data available

Additional information

no data available

SECTION 11: Toxicological information

Information on toxicological effects

Acute effects

Acute oral toxicity:

LD50 (oral. Rat): 5045 mg/kg (RTECS) (anhydrous)

Acute dermal toxicity:

LD50 (dermal. Rabbit): 12800 mg/kg (RTECS) (anhydrous)

Acute inhalation toxicity:

no data available

Irritant and corrosive effects

Primary irritation to the skin:

not applicable

Irritation to eyes:

Causes serious eye irritation.

Irritation to respiratory tract:

not applicable

Respiratory or skin sensitisation

In case of skin contact: not sensitising

After inhalation: not sensitising

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

not applicable

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Carcinogenicity**

No indication of human carcinogenicity.

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

No indications of human reproductive toxicity exist.

Aspiration hazard

not applicable

Other adverse effects

no data available

Additional information

no data available

SECTION 12: Ecological information

Ecotoxicity**Acute (short-term) fish toxicity:**

no data available

Chronic (long-term) fish toxicity:

no data available

Acute (short-term) daphnia toxicity:

no data available

Chronic (long-term) daphnia toxicity:

no data available

Acute (short-term) algae toxicity:

no data available

Chronic (long-term) algae toxicity:

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Partition coefficient: n-octanol/water: no data available

Mobility in soil:

no data available

Results of PBT/vPvB assessment

no data available

Other adverse effects

no data available

SECTION 13: Disposal considerations
Waste treatment methods
Appropriate disposal / Product

Dispose according to local legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste code product: no data available

Appropriate disposal / Package

Dispose according to local legislation. Handle contaminated packages in the same way as the substance itself.

Additional information

no data available

SECTION 14: Transport information
Land transport (ADR/RID/DOT)

UN-No.:	1219
Proper Shipping Name:	ISOPROPANOL
Class(es):	3
Classification code:	F1
Hazard label(s):	3
Packing group:	II
Environmental hazards:	No
Special precautions for user:	
Hazard identification number (Kemler No.):	33
Tunnel restriction code:	D/E

(Passage forbidden through tunnels of category D when carried in bulk or in tanks. Passage forbidden through tunnels of category E.)

Sea transport (IMDG)

UN-No.:	1219
Proper Shipping Name:	ISOPROPANOL
Class(es):	3
Classification code:	
Hazard label(s):	3
Packing group:	II
Environmental hazards:	No
MARINE POLLUTANT:	No
Special precautions for user:	
Segregation group:	-

EmS-No. F-E S-D
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not relevant

Air transport (ICAO-TI / IATA-DGR)

UN-No.:	1219
Proper Shipping Name:	ISOPROPANOL
Class(es):	3
Classification code:	F1
Hazard label(s):	3
Packing group:	II
Special precautions for user	not relevant

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

General rules

Water hazard class (WGK): slightly hazardous to water (WGK 1)

California Prop 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Chemical Safety Assessment

no data available

SECTION 16: Other information

Abbreviations and acronyms

ACGIH - American Conference of Governmental Industrial Hygienists
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
AGS - Committee on Hazardous Substances (Ausschuss für Gefahrstoffe)
CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures
DFG - German Research Foundation (Deutsche Forschungsgemeinschaft)
DOT – U.S. Department of Transportation
Gestis - Information system on hazardous substances of the German Social Accident Insurance (Gefahrstoffinformationssystem der Deutschen Gesetzlichen Unfallversicherung)
IATA-DGR - International Air Transport Association-Dangerous Goods Regulations
ICAO-TI - International Civil Aviation Organization-Technical Instructions
IMDG - International Maritime Code for Dangerous Goods
LTV - Long Term Value
NIOSH - National Institute for Occupational Safety and Health
OSHA - Occupational Safety & Health Administration
PBT - Persistent, Bioaccumulative and Toxic
RID - Regulation concerning the International Carriage of Dangerous Goods by Rail
STV - Short Term Value
SVHC - Substances of Very High Concern
vPvB - very Persistent, very Bioaccumulative

Additional information

Indication of changes: general update

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.