

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1120 Case



1120 Case

- **Watertight, crushproof, and dust proof**
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

1120 Case Configurations

Cat. #	Description
1120	1120 Case
1120NF	1120 Case (No foam)



Black



Silver



Orange



Yellow



Blue



OD Green*



Desert Tan

*OD Green available upon request

1120 Case Specifications

Exterior Dimensions (L x W x D)

8.12" x 6.56" x 3.56" (20.6 x 16.7 x 9 cm)

Lid Depth

0.50" (1.3 cm)

Weight w/Foam

1.23 lbs. (0.56 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

1120 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1120 Case Accessories

Cat. #	Description
1120PF	Special Application Panel Frame
1121	3 pc. Replacement Foam Set
1123	Replacement O-ring

Interior Dimensions (L x W x D)

7.25" x 4.75" x 3.06" (18.4 x 12.1 x 7.8 cm)

Bottom Depth

2.56" (6.5 cm)

Total Depth

3.06" (7.8 cm)

Weight w/o Foam

1.17 lbs. (0.53 kg)

Buoyancy Max.

5 lbs. (2.27 kg)

Pelican™ Products, Inc. Canada

10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586

[Click to contact us](#) • www.pelican.ca