

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES
1150
Case



1150 Case

- **Watertight, crushproof, and dust proof**
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

1150 Case Configurations

Cat. #	Description
1150	1150 Case
1150NF	1150 Case (No foam)



Black



Silver



Orange



Yellow



Blue



OD Green*



Desert Tan

*OD Green available upon request

1150 Case Specifications

Exterior Dimensions (L x W x D)

9.12" x 7.56" x 4.37" (23.2 x 19.2 x 11.1 cm)

Lid Depth

0.75" (1.9 cm)

Weight w/Foam

1.98 lbs. (0.9 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

1150 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1150 Case Accessories

Cat. #	Description
1150PF	Special Application Panel Frame
1151	3 pc. Replacement Foam Set
1153	Replacement O-ring

Interior Dimensions (L x W x D)

8.18" x 5.68" x 3.62" (20.8 x 14.4 x 9.2 cm)

Bottom Depth

2.87" (7.3 cm)

Total Depth

3.62" (9.2 cm)

Weight w/o Foam

1.76 lbs. (0.8 kg)

Buoyancy Max.

8 lbs. (3.63 kg)

Pelican™ Products, Inc. Canada

10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586

[Click to contact us](#) • www.pelican.ca