

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1200 Case



1200 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

1200 Case Configurations

Cat. #	Description
1200	1200 Case
1200NF	1200 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1200 Case Specifications

Exterior Dimensions (L x W x D)

10.62" x 9.68" x 4.87" (27 x 24.6 x 12.4 cm)

Lid Depth

1.18" (3 cm)

Weight w/Foam

2.87 lbs. (1.3 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

1200 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1200 Case Accessories

Cat. #	Description
1200PF	Special Application Panel Frame
1201	3 pc. Replacement Foam Set
1203	Replacement O-ring

Interior Dimensions (L x W x D)

9.25" x 7.12" x 4.12" (23.5 x 18.1 x 10.5 cm)

Bottom Depth

2.93" (7.4 cm)

Total Depth

4.11" (10.4 cm)

Weight w/o Foam

2.65 lbs. (1.2 kg)

Buoyancy Max.

12.02 lbs. (5.45 kg)

Pelican™ Products, Inc. Canada

10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586
[Click to contact us](#) • www.pelican.ca