

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

**CASES**  
**1300**  
**Case**



Black



Silver



Orange



Yellow



OD Green\*



Desert Tan

\*OD Green available upon request

**1300 Case**

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

**1300 Case Configurations**

Cat. #	Description
1300	1300 Case
1300NF	1300 Case (No foam)

**1300 Case Specifications**

**Exterior Dimensions (L x W x D)**

10.62" x 9.68" x 6.87" (27 x 24.6 x 17.4 cm)

**Lid Depth**

1.18" (3 cm)

**Weight w/Foam**

3.53 lbs. (1.6 kg)

**Range Temperature**

-10 / 210° F (-23 / 99° C)

**1300 Case Certificates**

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

**1300 Case Accessories**

Cat. #	Description
1200PF	Special Application Panel Frame
1203	Replacement O-ring
1301	4 pc. Replacement Foam Set
1400IP	Instapak Quick® RT

**Interior Dimensions (L x W x D)**

9.87" x 7.00" x 6.12" (25.1 x 17.8 x 15.5 cm)

**Bottom Depth**

4.93" (12.5 cm)

**Total Depth**

6.11" (15.5 cm)

**Weight w/o Foam**

3.09 lbs. (1.4 kg)

**Buoyancy Max.**

12.35 lbs. (5.6 kg)

Pelican™ Products, Inc. Canada

10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586  
Click to contact us • [www.pelican.ca](http://www.pelican.ca)