

 [Print](#) | [Close Window](#)

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1450 Case



1450 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

1450 Case Configurations

Cat. #	Description
1450	1450 Case
1450NF	1450 Case (No foam)
1454	1450 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1450 Case Specifications

Exterior Dimensions (L x W x D)

16.00" x 13.00" x 6.87" (40.6 x 33 x 17.4 cm)

Lid Depth

1.75" (4.4 cm)

Weight w/Foam

6.39 lbs. (2.9 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

Interior Dimensions (L x W x D)

14.62" x 10.18" x 6.00" (37.1 x 25.8 x 15.2 cm)

Bottom Depth

4.25" (10.8 cm)

Total Depth

6.00" (15.2 cm)

Weight w/o Foam

5.51 lbs. (2.5 kg)

Buoyancy Max.

30 lbs. (13.61 kg)

Personalized Nameplate Available

1450 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280

1450 Case Accessories

Cat. #	Description
1450PF	Special Application Panel Frame
1451	3 pc. Replacement Foam Set
1453	Replacement O-ring
1455	Padded Divider Set Only
1500IP	Instapak Quick® RT

Pelican™ Products, Inc. Canada
 10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586
 Click to contact us • www.pelican.ca