

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1650 Case



1650 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings

1650 Case Configurations

Cat. #	Description
1650	1650 Case
1650NF	1650 Case (No foam)
1654	1650 Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request

1650 Case Specifications

Exterior Dimensions (L x W x D)

30.75" x 20.50" x 11.62" (78.1 x 52 x 29.5 cm)

Interior Dimensions (L x W x D)

28.50" x 17.37" x 10.50" (72.4 x 44.1 x 26.7 cm)

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Lid Depth

1.87" (4.7 cm)

Bottom Depth

8.62" (21.9 cm)

Total Depth

10.49" (26.6 cm)

Weight w/Foam

35.49 lbs. (16.1 kg)

Weight w/o Foam

29.1 lbs. (13.2 kg)

Buoyancy Max.

181 lbs. (82.1 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

No. of Wheels

4

Personalized Nameplate Available

1650 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1650 Case Accessories

Cat. #	Description
1651	4 pc. Replacement Foam Set
1652	Pick 'N' Pluck™ Sections Only (set of 2)
1653	Replacement O-ring
1655	Padded Divider Set Only
1659	Photo/Lid Organizer for 1650 Case

Pelican™ Products, Inc. Canada
 10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586
 Click to contact us • www.pelican.ca